



The Village of Doylestown

Zoning Department

24 South Portage Street
Doylestown OH 44230



A VILLAGE WITH VALUES

A TOWN OF TRADITIONS

Date: _____

Permit No. _____

VILLAGE OF DOYLESTOWN JOBSITE MAINTENANCE & REQUIREMENTS

- All erosion/silt runoff control devices shall be in place prior to any excavation/construction beginning and remain in good working order until lawn has been established.
- Erosion control shall be designed to control erosion on-site, with the objective of eliminating or minimizing erosion or sedimentation impacts off-site. Techniques, devices, or measures used shall be in accordance with the standards adopted by the Village.
- Contractor shall be responsible for keeping the existing public streets free of mud from construction activity and shall clear public streets daily of mud deposited as a result of construction.
- All downspout and footer drain on new construction must be connected to the storm water system.
- All new sidewalks to existing sidewalks are to be doweled using #4 rebar
- Jobsite must remain clean with all construction debris properly disposed of (no onsite burning).
- Driveways shall not exceed twenty-five (25) feet in width at the *curb* line of the street, except where the Zoning Inspector finds that a greater width is necessary to accommodate the vehicles customarily using the driveway.
- Grass and sidewalks are to be done before residency. Extensions can be granted for winter months.

A citation maybe issued for anyone found in violation

Job Start Date: _____

Job Location: _____

Contractor: _____

Contact Person: _____

Phone# (____) _____ - _____

E-mail address: _____

Signature

Title